

BT PRIME MOVER

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ELECTRIC WALKIE COUNTERBALANCED STACKER								
CSX10 32.30 x 9.0 x OPEN	24	255	12-85-7	31.00	8.63	23.25	12-255A/B	N/A
	24	300	12-100-7	31.00	8.63	26.25	12-255A/B	N/A
CSX20/30/40 32.30 x 13.30 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

HT60W/60C HX65/80 32.00 x 13.50 x OPEN	24	425	12-85-11	31.50	12.88	23.25	120V AUTO BUILT IN CHGR	
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

MX50/65 32.00 x 8.00 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 32.00 x 13.50 x OPEN	24	425	12-85-11	31.50	12.88	23.25	120V AUTO BUILT IN CHGR	
	24	510	12-85-13	30.63	12.88	23.25	12-600B	12-600C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

BT PRIME MOVER TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ELECTRIC COUNTERBALANCED ORDER SELECTOR								
OE15C 32.00 x 8.00 x 24.50	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
OPTIONAL COMP. 32.00 x 13.50 x 26.50	12	935	6-85-23	27.13	13.00	23.25	N/A	6-875C
	12	1020	6-85-25	29.13	12.88	23.25	N/A	6-1050C
OPTIONAL COMP. 32.00 x 13.50 x 26.50	24	425	12-85-11	31.50	12.88	23.25	120V AUTO BUILT IN CHGR	
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

ELECTRIC COUNTERBALANCED ORDER SELECTOR								
OE30B 36.50 x 13.63 x 31.50	24	750	12-125-13	35.88	11.75	30.38	12-725B	12-725C
	24	850	12-170-11	35.38	13.13	30.38	12-875B	12-875C
	24	875	12-125-15	35.25	13.00	30.38	12-875B	12-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

ELECTRIC COUNTERBALANCED ORDER SELECTOR								
OE35 36.25 x 13.88 x 31.50	24	850	12-170-11	35.38	13.13	31.00	12-875B	12-875C
	24	875	12-125-15	35.25	13.00	31.00	12-875B	12-875C
OPTIONAL COMP. 38.25 x 13.88 x 31.50	36	625	18-125-11	38.00	13.25	31.00	18-600B	18-600C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

BT PRIME MOVER TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ELECTRIC LOW-LIFT PALLET TRUCK								
PE45R/60C/60W 32.00 x 13.50 x OPEN	24	425	12-85-11	31.50	12.88	23.25	120V AUTO BUILT IN CHGR	
	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

ELECTRIC LOW-LIFT PALLET TRUCK								
PMX 28.25 x 9.00 x 24.00	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
	24	300	12-100-7	25.50	8.69	26.25	12-255A/B	N/A
OPTIONAL COMP. 31.25 x 9.00 x 24.00	24	255	12-85-7	30.88	8.63	23.25	120V AUTO BUILT IN CHGR	
	24	255	12-85-7	31.00	8.63	23.25	12-255A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

PX40/40R 32.00 x 8.00 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

ELECTRIC WALKIE-RIDER LOW-LIFT PALLET TRUCK								
QMX 31.25 x 9.00 x 24.00	24	255	12-85-7	30.88	8.63	23.25	UTO BUILT IN	
	24	255	12-85-7	31.00	8.63	23.25	12-255A/B	N/A

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

BT PRIME MOVER TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ELECTRIC DEEP REACH TRUCK								
RC25/30/40 36.25 x 12.00 x 33.50	24	625	12-125-11	32.25	11.13	31.00	12-600B	12-600C
	24	600	12-150-9	35.38	10.88	31.00	12-600B	12-600C
	24	750	12-125-13	35.88	11.75	31.00	12-725B	12-725C
OPTIONAL COMP. RC30/40 36.25 x 16.50 x 33.75	24	850	12-170-11	35.38	13.13	31.00	12-875B	12-875C
	24	875	12-125-15	35.25	13.00	31.00	12-875B	12-875C
	24	1020	12-170-13	35.38	15.50	31.00	N/A	12-1050C

ABOVE REQUIRES: 175 BLUE CONN., OR OPTIONAL RECOMMENDED 350, POSITION-B, 15" LEAD LENGTH, W/CVR

ELECTRIC DEEP REACH TRUCK								
RDX30 38.75 x 16.40 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.75 x 20.90 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC LOW-LIFT PALLET TRUCK								
RMX50 31.75 x 8.13 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C
OPTIONAL COMP. 31.75 x 13.94 x OPEN	12	510	6-85-13	29.00	11.00	23.25	6-450B	6-450C
	12	1020	6-85-25	29.38	13.00	23.25	N/A	6-1050C
	12	600	6-100-13	29.00	11.00	26.25	6-600B	6-600C
	12	1200	6-100-25	29.38	12.88	26.25	N/A	6-1200C
	12	750	6-125-13	29.38	12.88	31.00	6-725B	6-725C
	12	1500	6-125-25	29.38	12.88	31.00	N/A	6-1450C

ABOVE REQUIRES: 175 GREY CONN., W/COVER

BT PRIME MOVER TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
RMX65/80 31.75 x 13.30 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

RR30C/RR34B/RR40B/ RR40BDR/RR45/ RR45DR/RS40C/RS50 38.75 x 14.50 x 32.00	24	875	12-170-11	35.38	13.13	30.38	N/A	12-875C
	24	850	12-125-17	38.25	13.50	30.38	N/A	12-875C
	24	1000	12-125-15	35.25	13.00	30.38	N/A	12-1050C
OPTIONAL COMP. 38.75 x 16.50 x 32.00	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
	24	1020	12-170-13	35.38	15.50	30.38	N/A	12-1050C
	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

ELECTRIC REACH TRUCK								
RRB5/RRE5 48.00 x 13.50 x 31.00	48	500	24-125-9	47.44	13.03	30.38	24-450B	24-450C
RRB6/RRE6 48.00 x 16.50 x 30.38	48	500	24-125-9	47.56	13.54	30.38	24-450B	24-450C

ABOVE REQUIRES: 350 CONNECTOR, W/O COVER

COMPACT ELECTRIC REACH TRUCK								
RRN2 42.00 x 13.50 x 31.00	48	375	24-125-7	37.88	12.50	30.38	24-380B	24-380C

ABOVE REQUIRES: 350 CONNECTOR, W/O COVER

BT PRIME MOVER TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER (1) PHASE	CHARGER (3) PHASE
				X	Y	Z		
COMPACT ELECTRIC REACH TRUCK								
RRN3 42.00 x 17.00 x 31.00	48	500	24-125-9	38.50	14.63	30.38	24-450B	24-450C

ABOVE REQUIRES: 350 CONNECTOR, W/O COVER

ELECTRIC REACH TRUCK								
RRX35 38.75 x 16.40 x 32.00	24	1020	12-170-13	35.38	15.50	30.38	N/A	12-1050C
	36	750	18-125-13	38.00	15.50	30.38	18-275B	18-725C
OPTIONAL COMP. 38.75 x 14.40 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 RED CONN. (24v), GREY (36v), POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC REACH TRUCK								
RRX45 38.75 x 16.40 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC REACH TRUCK								
OPTIONAL RRX45 38.75 x 20.90 x 32.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

SC20/25/30 31.30 x 13.75 x 24.60	12	850	6-85-21	24.88	12.88	23.25	6-875B	6-875C
	12	1020	6-85-25	29.13	12.88	23.25	N/A	6-1050C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

BT PRIME MOVER TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
OPTIONAL SC20/25/30 STANDARD SC40 32.50 x 14.00 x 24.60	24	510	12-85-13	30.63	12.88	23.25	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

SN20/30 32.00 x 8.00 x OPEN	12 12 12	510 600 750	6-85-13 6-100-13 6-125-13	30.88 30.88 30.88	7.75 7.75 7.75	23.25 26.25 31.00	6-450B 6-600B 6-725B	6-450C 6-600C 6-725C
OPTIONAL SN20/30, SR30 STANDARD SN40 32.00 x 13.50 x OPEN	12 24 24 24	765 510 600 750	6-85-19 12-85-13 12-100-13 12-125-13	31.25 30.63 30.88 30.88	13.13 12.88 12.88 12.88	23.25 23.25 26.25 31.00	6-725B 12-450B 12-600B 12-725B	6-725C 12-450C 12-600C 12-725C
SR30 31.38 x 13.75 x 24.75	12	765	6-85-19	31.25	13.13	23.25	6-725B	6-725C
OPTIONAL COMP. SR30 32.00 x 13.50 x OPEN	24 24 24	510 600 750	12-85-13 12-100-13 12-125-13	30.63 30.88 30.88	12.88 12.88 12.88	23.25 26.25 31.00	12-450B 12-600B 12-725B	12-450C 12-600C 12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

TE50/TT50 32.00 x 8.00 x OPEN	12 12 12	510 600 750	6-85-13 6-100-13 6-125-13	30.88 30.88 30.88	7.75 7.75 7.75	23.25 26.25 31.00	6-450B 6-600B 6-725B	6-450C 6-600C 6-725C
----------------------------------	----------------	-------------------	---------------------------------	-------------------------	----------------------	-------------------------	----------------------------	----------------------------

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

BT PRIME MOVER TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
TE70/TT70 32.00 x 13.25 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

ELECTRIC CENTER-CONTROL TOW TRACTOR								
TMX 31.75 x 13.30 x 32.00	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

ELECTRIC WALKIE ADJUSTABLE STRADDLE STACKER								
WSX20/25 27.38 x 9.00 x OPEN	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
	24	300	12-100-7	25.50	8.69	26.25	12-255A/B	N/A

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 15" LEAD LENGTH, W/COVER

ELECTRIC WALKIE STRADDLE STACKER								
WSX22 32.30 x 9.00 x OPEN	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
	24	300	12-100-7	25.50	8.69	26.25	12-255A/B	N/A
WSX30/40 32.30 x 13.30 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

Jun-98