

CATERPILLAR

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SIT-DOWN RIDER								
EC15/18 35.80 x 27.80 x 23.30	36	680	18-85H-17	33.25	25.75	22.63	18-725B	18-725C
	36	680	18-85H-17	32.25	26.75	22.63	18-725B	18-725C
	48	595	*24-85H-15	35.50	26.00	22.63	24-600B	24-600C
EC20/25 39.90 x 30.50 x 23.30	36	1020	18-85H-25	38.50	29.13	22.63	N/A	18-1050C
	48	765	24-85H-19	38.50	29.75	22.63	N/A	24-725C
EC25E/EC30 39.90 x 34.40 x 23.30	36	1190	*18-85H-29	38.50	33.63	22.63	N/A	18-1200C
	48	850	24-85H-21	38.50	33.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 24" LEAD LENGTH, W/O COVER

SIT-DOWN RIDER								
EP15T, F25/30 39.20 x 20.60 x 24.40	36	680	18-85H-17	38.00	19.88	22.63	18-725B	18-725C
	48	510	*24-85H-13	38.13	20.63	22.63	24-450B	24-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-D, 30" LEAD LENGTH, W/O COVER

SIT-DOWN RIDER								
EP18/20T, F35/FC40 39.20 x 24.90 x 24.40	36	750	18-85H-19	38.50	24.50	22.63	18-725B	18-725C
	36	850	18-85H-21	38.50	24.50	22.63	N/A	18-875C
	48	595	*24-85H-15	38.50	24.00	22.63	24-600B	24-600C
F40/50D, F40/50DSA 41.30 x 45.50 x 20.90	36	880	*18-55H-33	38.50	38.13	18.50	N/A	18-875C
	48	660	*24-55H-25	39.00	38.50	18.50	24-600B	24-600C

ABOVE REQUIRES: 350 GREY CONN., POSITION-D, 30" LEAD LENGTH, W/O COVER

CATERPILLAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SIT-DOWN RIDER								
F60DSA 45.50 x 49.20 x 20.90	36	880	*18-55H-33	38.50	38.13	18.50	N/A	18-875C
	48	770	*24-55H-29	45.00	38.50	19.50	N/A	24-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-D, 30" LEAD LENGTH, W/O COVER

SIT-DOWN RIDER								
M25/30/35D MC40D 34.50 x 28.00 x 24.13	36	680	18-85H-17	33.25	25.75	22.63	18-725B	18-725C
	36	765	*18-85H-19	32.00	28.00	22.63	18-725B	18-725C
	48	510	24-85H-13	31.00	25.75	22.63	24-450B	24-450C
M40D/DSA 40.70 x 30.50 x 23.58	36	1020	18-85H-25	38.50	29.13	22.63	N/A	18-1050C
	48	765	24-85H-19	38.50	29.75	22.63	N/A	24-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/O COVER

SIT-DOWN RIDER								
M50D/DSA 40.20 x 33.30 x 23.58	36	1105	18-85H-27	38.50	31.38	22.63	N/A	18-1050C
	48	850	24-85H-21	38.50	33.00	22.63	N/A	24-875C
MC60DSA 40.20 x 34.40 x 23.60	36	1190	*18-85H-29	38.50	34.00	22.63	N/A	18-1200C
	48	850	24-85H-21	38.50	33.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

SIT-DOWN RIDER								
M70/80/100/120D 43.3 x 40.00 x 24.00	36	1360	*18-85H-33	38.50	38.13	22.63	N/A	18-1450C
	48	1105	*24-85H-27	42.00	38.50	22.63	N/A	24-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/O COVER

CATERPILLAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
CENTER-RIDE TOW TRACTOR								
NDC100 31.00 x 13.12 x 24.00	24	425	12-85-11	31.50	12.88	23.25	AUTO BUILT IN 12-450B	
	24	510	12-85-13	30.63	12.88	23.25		12-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

WALKIE STACKER										
NFP/NSP22 10.00 x 6.50	12	60								
			REQUIRES (2) 12V BATTERIES							
			BATTERIES NOT AVAILABLE							

NARROW AISLE ORDERPICKER								
NOR30 31.00 x 13.00 x 30.88	24	600	12-100-13	30.88	12.88	25.63	12-600B	12-600C
	24	725	12-125-13	30.88	12.88	30.38	12-725B	12-725C

ABOVE REQUIRES: 350 RED CONN., POSITION-C, 12" LEAD LENGTH, W/O COVER

ORDERPICKER								
NOR30P 36.38 x 14.00 x 30.88	24	850	12-170-11	35.38	13.13	30.38	N/A	12-875C
	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
OPTIONAL COMP. 38.38 x 14.00 x 30.88	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 RED CONN.(24v), GREY (36v), POSITION-C, 12" LEAD LENGTH, W/O COVER

CENTER-RIDE, SIDE STANCE RIDER								
NPC60/NPS60 32.00 x 13.44 x 24.00	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

CATERPILLAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE								
NPP40 28.12 x 8.88 x 26.50	24	255	12-85-7	25.50	8.63	23.25	12-255A	12-255B
	24	300	12-100-7	25.50	8.50	26.25	12-255A	12-255B

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 12" LEAD LENGTH, W/COVER

WALKIE								
NPP60/NPV60 32.00 x 9.19 x 24.0	24	255	12-85-7	31.00	8.63	23.25	12-255A	12-255B
OPTIONAL COMP. 32.00 x 13.44 x 24.00	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
NPC80/NPV80 31.50 x 13.44 x 31.00	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

DOUBLE-REACH TRUCK								
NRDR25 38.67 x 14.25 x 31.62	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
NRDR25/30P NRR30/35/40/45P 38.67 x 16.25 x 31.62	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.67 x 21.25 x 31.62	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

CATERPILLAR TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE STACKER REACH TRUCK								
NRP30 31.90 x 13.40 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/COVER

STRADDLE TRUCK								
NSR30/40 NRR30/35/40 38.67 x 14.25 x 31.62	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
OPTIONAL COMP. NSR30/40 38.67 x 16.25 x 31.62	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C

ABOVE REQUIRES: 350 RED CONN., POSITION-B, 11" LEAD LENGTH, W/O COVER

Jun-98

