

KOMATSU

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
FB10/13 M-1 38.90 x 17.70 x 25.40	48	425	24-85-11	37.88	17.63	22.63	24-450B	24-450C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

FB10/13MU-1 38.90 x 17.70 x 25.40	36	510	18-85-13	38.38	15.50	22.63	18-450B	18-450C
--------------------------------------	----	-----	----------	-------	-------	-------	---------	---------

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

FB13MU-1 REQUIRES 16" LEADS

THREE WHEEL COUNTERBALANCED								
FB10SH-1 31.88 x 18.88 x 23.00	36	425	18-85-11	31.88	17.75	22.63	18-450B	18-450C
	48	340	24-85-9	31.88	18.13	22.63	18-380B	18-380C
OPTIONAL COMP. 36.75 x 23.62 x 23.00	36	595	18-85-15	35.38	19.31	22.63	18-600B	18-600C
	48	425	24-85-11	31.88	21.88	22.63	24-450B	24-450C
FB15M-1 38.90 x 21.30 x 25.40	48	510	24-85-13	38.00	21.00	22.63	24-450B	24-450C
FB15MK-2 39.20 x 20.60 x 24.00	36	680	18-85-17	38.00	19.88	22.63	18-725B	18-725C
FB15/18M/MK-2 39.20 x 20.60 x 24.00	24	1020	12-85-25	38.88	19.31	22.63	N/A	12-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

KOMATSU TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
FB15MU-1 38.90 x 21.30 x 25.40	36	680	18-85-17	38.00	19.88	22.63	18-725B	18-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

FOUR WHEEL COUNTERBALANCED								
FB15SH-1 36.88 x 26.75 x 23.00	36	765	18-85-19	35.25	25.75	22.63	18-725B	18-725C
	48	595	24-85-15	35.50	26.00	22.63	24-600B	24-600C
OPTIONAL COMP. 31.88 x 22.00 x 23.00	36	510	18-85-13	30.88	19.25	22.63	18-450B	18-450C
	48	340	24-85-9	31.88	18.13	22.63	18-380B	18-380C
FB15/18SH-5 36.75 x 26.75 x 23.00	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	36	765	18-85-19	35.25	25.75	22.63	18-725B	18-725C
	48	595	24-85-15	35.50	26.00	22.63	24-600B	24-600C
FB15/18SH/SHE-6 36.20 x 27.00 x 23.70	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	36	765	18-85-19	35.25	25.75	22.63	18-725B	18-725C
	48	595	24-85-15	35.50	26.00	22.63	24-600B	24-600C
FB20/25SH-2 39.00 x 28.00 x 23.00	36	850	18-85-21	38.50	24.50	22.63	N/A	18-875C
	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
OPTIONAL COMP. 35.38 x 23.00 x 23.00	36	595	18-85-15	35.38	19.31	22.63	18-600B	18-600C
	48	425	24-85-11	31.88	21.88	22.63	24-450B	24-450C
FB20/25SH-3 39.20 x 28.00 x 23.00	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

KOMATSU TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
FOUR WHEEL COUNTERBALANCED								
OPTIONAL FB25SH-3 39.20 x 34.00 x 23.00	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

FOUR WHEEL COUNTERBALANCED								
FB20/25SH/SHE-4**	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
FB25SHH/SHHE-4**	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C
FB20/25SHG/SHGE-4** FB25SHHG/SHHGE-4** 39.20 x 33.40 x 23.60	36	1020	18-85-25	38.50	29.13	22.63	N/A	18-1050C
	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	765	24-85-19	38.50	29.75	22.63	N/A	24-725C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
FB30SH/SHE/SHH-4** 39.20 x 33.40 x 23.60	36	1020	18-85-25	38.50	29.13	22.63	N/A	18-1050C
	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	765	24-85-19	38.50	29.75	22.63	N/A	24-725C22
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C22

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

** REQUIRES "EE" RATED BATTERY TO MAINTAIN UL RATING

FB30S-2 39.20 x 34.00 x 23.00	48	765	24-85-19	38.50	29.75	22.63	N/A	24-725C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 18" LEAD LENGTH, W/O COVER

DOUBLE REACH								
FR15DR-2A 38.75 x 16.4 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

KOMATSU TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
SINGLE REACH								
FR18S-2A 38.50 x 16.40 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.75 x 14.40 x 32.00	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 RED CONN. (24v), GREY (36v), POSITION-C, 15" LEAD LENGTH, W/O COVER

SINGLE REACH								
FR23S-2A 38.75 x 16.40 x 32.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
OPTIONAL COMP. 38.75 x 20.90 x 32.00	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-C, 15" LEAD LENGTH, W/O COVER

ELECTRIC COUNTERBALANCED ORDER SELECTOR								
MPF15-1A 36.50 x 13.88 x 31.50	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
39.00 x 13.88 x 31.50	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 GREY CONN., 18" LEAD LENGTH, W/O COVER

LOW LIFT PALLET TRUCK								
MWE31/36-1A 31.75 x 13.30 x OPEN	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 RED CONN., 20" LEAD LENGTH, W/COVER

KOMATSU TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- TAGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
COUNTERBALANCED STACKER								
MWH10/15/20C-1A	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
MWH15/20-1A	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
MWH15R-1A	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
32.30 x 13.30 x OPEN								

ABOVE REQUIRES: 175 RED CONN., W/COVER

LOW LIFT PALLET TRUCK								
MWL22-1A 29.25 x 9.00 x 24.00	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
OPTIONAL COMP. 31.25 x 9.00 x 24.00	24	255	12-85-7	31.00	8.50	23.25	12-255A/B	N/A

ABOVE REQUIRES: 175 RED CONN., 20" LEAD LENGTH, W/COVER

LOW LIFT PALLET TRUCK								
MWL25-1A	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
31.75 x 13.30 x OPEN	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
	12	750	6-125-13	30.88	7.75	31.00	6-725B	6-725C

ABOVE REQUIRES: 175 YELLOW CONN., 18" LEAD LENGTH, W/COVER

LOW LIFT PALLET TRUCK								
MWL31/36-1A	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
31.75 x 13.30 x OPEN	24	600	12-100-13	30.88	12.88	26.25	12-600B	12-600C
	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 RED CONN., 20" LEAD LENGTH, W/COVER

Jun-98

|

