

RAYMOND

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
ELF								
O19 31.00 x 13.00 x 24.00	24	510	12-85-13	30.63	12.88	23.25	12-450B	12-450C
WALKIE PALLET TRUCKS								
101T-F40L 28.00 x 8.75 x 26.50	24	255	12-85-7	25.50	8.63	23.25	12-255A/B	N/A
111TM-F60L 31.00 x 8.75 x 31.00	24 24	255 255	12-85-7 12-85-7	25.50 31.00	8.63 8.63	23.25 23.25	12-255A/B 12-255A/B	N/A N/A
RIDER PALLET JACKS								
112TM-F60L 113TM-FRC60L 31.00 x 13.00 x 31.00	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C
TOW TRUCKS								
114TM-TOW 31.00 x 13.00 x 31.00	24	750	12-125-13	30.88	12.88	31.00	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 12" LEAD LENGTH, W/COVER

STAND-UP COUNTERBALANCE								
630 PACER 38.75 x 16.25 x 31.00	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
640 PACER 38.75 x 21.25 x 31.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 8" LEAD LENGTH, W/O COVER

RAYMOND TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
STAND-UP COUNTERBALANCE								
650 PACER 38.75 x 21.25 x 31.00	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 13" LEAD LENGTH, W/O COVER

STAND-UP COUNTERBALANCE								
DSS300/350 38.50 x 16.25 x 32.30	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN., W/O COVER

ORDERPICKERS								
OPC30T 31.00 x 13.00 x 30.88	24	750	12-125-13	30.88	12.88	30.38	12-725B	12-725C

ABOVE REQUIRES: 350 RED CONN. POSITION-C, 20" LEAD LENGTH, W/O COVER

ORDERPICKERS								
OPC30TT 36.88 x 14.00 x 30.88	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C
38.38 x 13.69 x 30.88	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 RED CONN. POSITION-C, 12" LEAD LENGTH, W/O COVER

NARROW AISLE REACH								
R30TN/TT 38.63 x 14.20 x 31.62	24 24	875 1000	12-125-15 12-125-17	38.25 38.25	12.00 13.50	30.38 30.38	N/A N/A	12-875C 12-1050C

ABOVE REQUIRES: 350 GREY CONN. POSITION-B, 11" LEAD LENGTH, W/O COVER

RAYMOND TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
NARROW AISLE REACH								
R30/TT/TN 38.63 x 14.20 x 31.62	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
R30TT 38.62 x 16.12 x 31.62	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C

ABOVE REQUIRES: 350 GREY CONN. POSITION-B, 11" LEAD LENGTH, W/O COVER

NARROW AISLE REACH								
R35TT 38.63 x 14.12 x 31.62	24	875	12-125-15	38.25	12.00	30.38	N/A	12-875C
	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
R35/40TT/TT-M 38.62 x 16.12 x 31.62	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
R40TN/TT 38.63 x 14.12 x 31.62	24	875	12-125-15	38.25	12.00	30.38	N/A	12-875C
	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
R45TT/TT-M 38.88 x 16.12 x 31.63	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
R45TT-M 38.88 x 21.12 x 31.63	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C
R45TT-MB 38.88 x 21.12 x 31.62	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 RED CONN. (24v), GREY (36v), POSITION-B, 11" LEAD LENGTH, W/O COVER

RAYMOND TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
NARROW AISLE DEEP REACH								
DR25TT 38.62 x 14.12 x 31.62	24	875	12-125-15	38.25	12.00	30.38	N/A	12-875C
	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
DR25/30TT 38.62 x 16.12 x 31.62	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
DR30TT-B 38.62 x 21.12 x 31.62	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 RED CONN. (24v), GREY (36v), POSITION-B, 11" LEAD LENGTH, W/O COVER

VERY NARROW AISLE SWING REACH								
537CSRT 44.38 x 21.25 x 32.50	48	750	24-125-13	43.50	21.00	30.38	24-725B	24-725C

ABOVE REQUIRES: 350 BLUE CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

Jun-98