

YALE

LIFT TRUCK SPECIFICATIONS

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE PALLET TRUCK								
MPB040AC 28.97 x 7.69 x 24.30	24	170	12-85-5	24.75	6.63	23.25	12-180A/B	N/A
MLW040/060 MPW045DA/MPW060 31.75 x 8.09 x OPEN	12 12	510 600	6-85-13 6-100-13	30.88 30.88	7.75 7.75	23.25 26.25	6-450B 6-600B	6-450C 6-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/COVER

WALKIE PALLET TRUCK								
MLW040/060 MPW060/080 32.00 x 13.40 x OPEN	24 24	510 600	12-85-13 12-100-13	30.63 30.88	12.88 12.88	23.25 26.25	12-450B 12-600B	12-450C 12-600C
RIDER PALLET TRUCK								
MPE060 32.00 x 9.00 x OPEN	12 12	510 600	6-85-13 6-100-13	30.88 30.88	7.75 7.75	23.25 26.25	6-450B 6-600B	6-450C 6-600C
MPE060/080 MPC060/080, MTR 32.00 x 13.40 x OPEN	24 24	510 600	12-85-13 12-100-13	30.63 30.88	12.88 12.88	23.25 26.25	12-450B 12-600B	12-450C 12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

WALKIE LIFT TRUCK								
MCW020/025/030/040 31.87 x 13.38 x OPEN	24 24	510 600	12-85-13 12-100-13	30.63 30.88	12.88 12.88	23.25 26.25	12-450B 12-600B	12-450C 12-600C

ABOVE REQUIRES: 175 RED CONN., POSITION-B, 20" LEAD LENGTH, W/COVER

YALE TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
WALKIE STRADDLE & REACH TRUCK								
MSW020/030, MRW020 35.40 x 8.12 x OPEN	12	510	6-85-13	30.88	7.75	23.25	6-450B	6-450C
	12	600	6-100-13	30.88	7.75	26.25	6-600B	6-600C
MSW020/030/040 MRW020/030 35.40 x 13.50 x OPEN	24	595	12-85-15	35.38	13.00	23.25	12-600B	12-600C
	24	700	12-100-15	35.38	12.88	26.25	12-725B	12-725C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/COVER

ORDER SELECTORS								
OS030BC/SS030BC 39.00 x 14.60 x 31.50	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C
	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/O COVER

ORDER SELECTORS								
OS030E 36.00 x 13.50 x 25.00	24	595	12-85-15	35.38	13.00	23.25	12-600B	12-600C

ABOVE REQUIRES: 175 GREY CONN., POSITION-B, 16" LEAD LENGTH, W/O COVER

NARROW AISLE STRADDLE & REACH TRUCK								
NS040AD/NR035/040AC 38.88 x 12.50 x 31.50	24	875	12-125-15	38.25	12.00	30.38	N/A	12-875C
NS040AD/NR035/040AC NDR030AC 38.88 x 14.60 x 31.50	24	1000	12-125-17	38.25	13.50	30.38	N/A	12-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/O COVER

YALE TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
NARROW AISLE STRADDLE & REACH TRUCK								
NS040/050AD NR035/040/045AC NDR030AC 38.88 x 14.60 x 31.50	36	625	18-125-11	38.00	13.25	30.38	18-600B	18-600C
NS040AD/NR035/040AC NDR030AC 38.88 x 16.60 x 31.50	24	1125	12-125-19	38.38	15.00	30.38	N/A	12-1200C
NS040/050AD NR035/040/045AC NDR030AC 38.88 x 16.60 x 31.50	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
NR035/045BC NDR030BC 38.88 x 18.80 x 31.50	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
NR035/045BC NDR030BC 38.88 x 21.10 x 31.50	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/O COVER

THREE WHEEL STAND UP RIDER								
ESC020/025/030A 36.50 x 13.60 x 31.30	24	875	12-125-15	35.25	13.00	30.38	N/A	12-875C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 20" LEAD LENGTH, W/O COVER

YALE TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
THREE WHEEL STAND UP RIDER								
ESC030/035ZA 38.75 x 16.12 x 31.50	36	750	18-125-13	38.00	15.50	30.38	18-725B	18-725C
38.81 x 18.12 x 31.50	36	875	18-125-15	38.50	17.88	30.38	N/A	18-875C
ESC040/050ZA 38.88 x 20.75 x 31.50	36	1000	18-125-17	38.50	20.13	30.38	N/A	18-1050C

ABOVE REQUIRES: 350 GREY CONN., POSITION-B, 30" LEAD LENGTH, W/O COVER

THREE WHEEL LIFT TRUCK								
ERPS30TF 39.00 x 16.70 x 26.12	36	600	18-100-13	38.00	15.50	25.63	18-600B	18-600C
	48	400	24-100-9	38.50	14.63	25.63	18-380B	18-380C
ERP030TF 39.00 x 21.50 x 26.12	36	800	18-100-17	38.50	20.13	25.63	N/A	18-875C
	48	600	24-100-13	38.13	20.63	25.63	24-600B	24-600C
ERP035/040TF 39.00 x 25.20 x 26.12	36	1000	18-100-21	38.50	24.63	25.63	N/A	18-1050C
	48	700	24-100-15	38.25	23.75	25.63	N/A	24-725C

ABOVE REQUIRES: 350 GREY CONN. (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, W/O COVER

FOUR WHEEL CUSHION TIRE TRUCK								
ERC030/040AF 34.57 x 27.36 x 24.29	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	48	510	24-85-13	31.00	25.75	22.63	24-450B	24-450C
35.79 x 27.36 x 24.29	36	680	18-85-17	33.25	25.75	22.63	18-725B	18-725C
	48	595	24-85-15	35.50	26.00	22.63	24-600B	24-600C

ABOVE REQUIRES: 350 GREY CONN. (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, W/O COVER

YALE TRUCKS CONTINUED...

TRUCK MODEL COMPARTMENT	VOLT- AGE	AMPS	BATTERY TYPE	DIMENSIONS			CHARGER	CHARGER
				X	Y	Z	(1) PHASE	(3) PHASE
FOUR WHEEL CUSHION TIRE TRUCK								
ERC040/050RF/ZF 38.86 x 27.36 x 24.41	36	935	18-85-23	38.50	26.75	22.63	N/A	18-875C
	48	680	24-85-17	38.50	27.00	22.63	N/A	24-725C
38.86 x 30.75 x 24.41	36	1020	18-85-25	38.50	29.13	22.63	N/A	18-1050C
	48	765	24-85-19	38.50	29.75	22.63	N/A	24-725C
ERC040/050/060RF/ZF 38.86 x 33.15 x 24.41	36	1105	18-85-27	38.50	31.38	22.63	N/A	18-1050C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
ERC065RF/ZF 38.86 x 36.54 x 24.41	36	1190	18-85-29	38.50	33.63	22.63	N/A	18-1200C
	36	1275	18-85-31	38.50	36.38	22.63	N/A	18-1200C
	48	850	24-85-21	38.50	33.00	22.63	N/A	24-875C
	48	935	24-85-23	38.50	36.00	22.63	N/A	24-875C
ERC070/080HD 44.10 x 39.20 x 23.15	36	1275	18-85-31	38.50	36.38	22.63	N/A	18-1200C
	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	935	24-85-23	38.50	36.00	22.63	N/A	24-875C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C
ERC100HD 44.10 x 39.20 x 23.15	36	1275	18-85-31	38.50	36.38	22.63	N/A	18-1200C
	36	1360	18-85-33	38.50	38.13	22.63	N/A	18-1450C
	48	935	24-85-23	38.50	36.00	22.63	N/A	24-875C
	48	1020	24-85-25	39.00	38.50	22.63	N/A	24-1050C
ERC100/120HD 44.10 x 45.70 x 23.15	36	1530	(2)18-85-19	44.88	38.50	22.63	N/A	18-1450C
	48	1190	24-85-29	45.00	38.50	22.63	N/A	24-1200C

ABOVE REQUIRES: 350 GREY CONN. (36v), BLUE (48v), POSITION-B, 30" LEAD LENGTH, W/O COVER

Jun-98